

BURGESS

WELL COMPANY, INC.

724 East Highway 6 Minden, Nebraska 68959-2569 U.S.A.
 Phone: (308) 832-1645 or 800-762-0331
 Fax: (308) 832-0170 or 888-241-7580
 E-Mail: burgesswell@rcom-ne.com
 http://www.burgesswell.com



"EON" ASR Fiberglass Well Casing

**Certified to
NSF/ANSI 61**

DIMENSIONAL SPECIFICATIONS: .250" Wall 1/1/2009

PIPE SIZE (Inches)	Nominal ID (Inches)	Nominal OD (Inches)	Nominal Wall (Inches)	Coupling Diameter Diameter (in.) x Length (in.)	
4 1/2	4.50	5.00	0.250	7.5	5 7/8
6 1/2	6.50	7.00	0.250	9.5	7 7/8
8 1/2	8.50	9.00	0.250	11.5	7 7/8
10 1/2	10.50	11.00	0.250	14.5	9 7/8
12	12.00	12.50	0.250	16	9 7/8
14	14.00	14.50	0.250	18	9 7/8
16	16.00	16.50	0.250	20	9 7/8

PERFORMANCE RATINGS (-60 TO + 200° F) Polyester Resin Based.

Pipe Size Inches	Pipe Internal Pressure Rating (psi)	Collapse Pressure Resistance (psi)			Tensile Strength Rated (lbs.)	Standard Nominal Lbs./ Ft.	Joint Pressure Rating (psi)
		Std.	24" Corr.	18" Corr.			
4 1/2	400	850	1,725	2,050	14,250	3.3	400
6 1/2	275	310	635	770	20,250	5.0	275
8 1/2	200	145	300	365	26,250	6.0	200
10 1/2	175	80	165	200	32,250	7.0	175
12	150	55	115	165	36,750	7.75	150
14	130	35	70	85	42,750	9.25	130
16	115	25	45	60	48,750	10.5	115