

BURGESS

WELL COMPANY, INC.

724 East Highway 6 Minden, Nebraska 68959-2569 U.S.A.
 Phone: (308) 832-1645 or 800-762-0331
 Fax: (308) 832-0170 or 888-241-7580
 E-Mail: burgesswell@rcom-ne.com
<http://www.burgesswell.com>



"EON" ASR Fiberglass Well Casing

**Certified to
NSF/ANSI 61**

DIMENSIONAL SPECIFICATIONS: .375" Wall 1/1/2008

PIPE SIZE (Inches)	Nominal ID (Inches)	Nominal OD (Inches)	Nominal Wall (Inches)	Coupling Diameter Diameter (in.) x Length (in.)	
4 1/2	4.50	5.25	0.375	7.5	5 7/8
6 1/2	6.50	7.25	0.375	9.5	7 7/8
8 1/2	8.50	9.25	0.375	11.5	7 7/8
10 1/2	10.50	11.25	0.375	14.5	9 7/8
12	12.00	12.75	0.375	16	9 7/8
14	14.00	14.75	0.375	18	9 7/8
16	16.00	16.75	0.375	20	9 7/8

PERFORMANCE RATINGS (-60 TO + 200° F) Polyester Resin Based.

Pipe Size Inches	Pipe Internal Pressure Rating	Collapse Pressure Resistance (psi)			Tensile Strength Rated (lbs.)	Standard Nominal Lbs./ Ft.	Joint Pressure Rating (psi)
		Std.	24" Corr.	18"corr.			
4 1/2	575 psi	3,380	4,940	5,545	21,750	4.4	575
6 1/2	400 psi	1,280	1,950	2,200	30,975	6.3	400
8 1/2	300 psi	615	950	1,075	39,975	8.3	300
10 1/2	250 psi	340	530	605	49,000	10.2	250
12	225 psi	230	365	415	55,750	11.6	225
14	200 psi	150	240	270	64,750	13.5	200
16	175 psi	115	165	235	73,750	15.4	175

"ALL PIPE IS MANUFACTURED TO MEET THE ABOVE LISTED SPECIFICATIONS."